SAFETY DATA SHEET

Section 1. Identification

Product name	Molub-Alloy GM 1500
SDS #	468757
Historic SDS #:	75250
Code	468757-US69
Relevant identified uses	of the substance or mixture and uses advised against
Product use	Gear lubricant . For specific application advice see appropriate Technical Data Sheet or consult our company representative.
Manufacturer	Castrol Industrial North America, Inc. 150 W. Warrenville Road Naperville, IL 60563
Supplier	Castrol Industrial North America, Inc. 150 W. Warrenville Road Naperville, IL 60563 Product Information: +1-877-641-1600
EMERGENCY SPILL INFORMATION:	1 (800) 424-9300 CHEMTREC (USA)

Section 2. Hazards identification

OSHA/HCS status	This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).	
Classification of the substance or mixture	Not classified.	
Substance of mixture		
GHS label elements		
Signal word	No signal word.	
Hazard statements	No known significant effects or critical hazards.	
Precautionary statements		
Prevention	Not applicable.	
Response	Not applicable.	
Storage	Not applicable.	
Disposal	Not applicable.	
Hazards not otherwise classified	Defatting to the skin.	

Section 3. Composition/information on ingredients

Highly refined base oil and additives.

Substance/mixture Mixture		
Ingredient name	CAS number	%
Base oil - highly refined	Varies	≥50 - <75
Base oil - highly refined	Varies	≥1 - <3
Phosphoric acid esters, amine salt	Proprietary	≥1 - <3
Soybean oil	8001-22-7	≥1 - <3

Product name	Molub-Alloy GM 1500		Product code	468757-US69	Page: 1/9
Version 1	Date of issue 03/11/2015.	Format	US	Language	ENGLISH
			(US)		(ENGLISH)

Section 3. Composition/information on ingredients

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.	
Skin contact	Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughl before reuse. Get medical attention if symptoms occur.	
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.	
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.	
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.	

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects.
Specific treatments	No specific treatment.

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet.
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	Combustion products may include the following: carbon dioxide carbon monoxide sulfur oxides
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency	No action shall be taken involving any personal risk or without suitable training.	
personnel	Evacuate surrounding areas. Keep unnecessary and unprotected personnel from	
	entering. Do not touch or walk through spilled material. Put on appropriate personal	
	protective equipment. Floors may be slippery; use care to avoid falling.	

Product name	Molub-Alloy GM 1500		Product code	468757-US69	Page: 2/9
Version 1	Date of issue 03/11/2015.	Format	US	Language	ENGLISH
			(US)		(ENGLISH)

Section 6. Accidental release measures

For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in
	Section 8 on suitable and unsuitable materials. See also the information in "For non- emergency personnel".
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for cor	ntainment and cleaning up
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling	
Protective measures	Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Base oil - highly refined	ACGIH TLV (United States). TWA: 5 mg/m ³ 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction OSHA PEL (United States). TWA: 5 mg/m ³ 8 hours. Issued/Revised: 6/1993
Base oil - highly refined	ACGIH TLV (United States). TWA: 5 mg/m ³ 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction OSHA PEL (United States). TWA: 5 mg/m ³ 8 hours. Issued/Revised: 6/1993
Soybean oil	OSHA PEL (United States). TWA: 5 mg/m ³ 8 hours. Issued/Revised: 6/1993 Form: Respirable fraction (Vegetable oil Mist) TWA: 15 mg/m ³ 8 hours. Issued/Revised: 6/1993 Form: Total dust (Vegetable oil Mist)

Product name	Molub-Alloy GM 1500		Product code	468757-US69	Page: 3/9
Version 1	Date of issue 03/11/2015.	Format	US	Language	ENGLISH
			(US)		(ENGLISH)

Section 8. Exposure controls/personal protection

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Appropriate engineering controls	All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	Safety glasses with side shields.
Skin protection	
Hand protection	Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.
	Consult your supervisor or Standard Operating Procedure (S.O.P) for special handling instructions.
Body protection	Use of protective clothing is good industrial practice. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Product name	Molub-Alloy GM 1500		Product code	468757-US69	Page: 4/9
Version 1	Date of issue 03/11/2015.	Format	US	Language	ENGLISH
			(US)		(ENGLISH)

Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	Liquid.
Color	Black.
Odor	Mild.
Odor threshold	Not available.
рН	Not available.
Melting point	Not available.
Boiling point	Not available.
Flash point	Open cup: 227°C (440.6°F) [Cleveland.]
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable. Based on - Physical state
Lower and upper explosive (flammable) limits	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Density	<1000 kg/m³ (<1 g/cm³) at 25°C
Solubility	insoluble in water.
Partition coefficient: n- octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Kinematic: 1500 mm²/s (1500 cSt) at 40°C

Section 10. Stability and reactivity

Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.	
Chemical stability	The product is stable.	
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not occur.	
Conditions to avoid	No specific data.	
Incompatible materials	Reactive or incompatible with the following materials: oxidizing materials, acids and alkalis.	
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.	

Section 11. Toxicological information

Information on toxicological effects				
Aspiration hazard				
Name		Result		
Base oil - highly refined		ASPIRATION HAZARD - Category 1		
Information on the likely Routes of entry anticipated: Dermal, Inhalation. routes of exposure Potential acute health effects				
Eye contact No know	vn significant effects or critical haz	zards.		
Product name Molub-Alloy GM 1500	Produc	t code 468757-US69 Page: 5/9		
Version 1 Date of issue 03/11/2015	. Format US	Language ENGLISH		
	(US)	(ENGLISH)		

Section 11. Toxicological information

Skin contact	No known significant effects or critical hazards.		
Inhalation	Vapor inhalation under ambient conditions is not normally a problem due to low vapor pressure.		
Ingestion	No known significant effects or critical hazards.		
Symptoms related to the phys	ical, chemical and toxicological characteristics		
Eye contact	No specific data.		
Skin contact	Adverse symptoms may include the following: irritation dryness cracking		
Inhalation	May be harmful by inhalation if exposure to vapor, mists or fumes resulting from thermal decomposition products occurs.		
Ingestion	No specific data.		
	s and also chronic effects from short and long term exposure		
<u>Short term exposure</u>			
Potential immediate effects	Not available.		
Potential delayed effects	Not available.		
Long term exposure			
Potential immediate effects	Not available.		
Potential delayed effects	Not available.		
Potential chronic health effe	<u>ots</u>		
General	No known significant effects or critical hazards.		
Carcinogenicity	No known significant effects or critical hazards.		
Mutagenicity	No known significant effects or critical hazards.		
Teratogenicity	No known significant effects or critical hazards.		
Developmental effects	No known significant effects or critical hazards.		
Fertility effects	No known significant effects or critical hazards.		

Numerical measures of toxicity Acute toxicity estimates

Route	ATE value
Oral	37697.9 mg/kg

Section 12. Ecological information

Toxicity

No testing has been performed by the manufacturer.

Persistence and degradability

Expected to be biodegradable.

Bioaccumulative potential

Not available.

Mobility in soil

Product name	Molub-Alloy GM 1500		Product code	468757-US69	Page: 6/9
Version 1	Date of issue 03/11/2015.	Format	US	Language	ENGLISH
			(US)		(ENGLISH)

Section 12. Ecological information

Soil/water partition
coefficient (Koc)
Mobility

Not available.

Non-volatile. Liquid. insoluble in water.

Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name		-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Additional information	Special provisions Petroleum oil, not regulated in containers less than 3500 gallons.	-	-	-

Special precautions for user No

Not available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not available.

Section 15. Regulatory information

U.S. Federal regulations United States inventory

All components are listed or exempted.

(TSCA 8b) SARA 302/304


Composition/information on ingredients

No products were found

No products were found.	
SARA 311/312	
Classification	Not applicable.
<u>SARA 313</u>	
Form R - Reporting requirements	This product does not contain any hazardous ingredients at or above regulated thresholds.
Supplier notification	This product does not contain any hazardous ingredients at or above regulated thresholds.
State regulations	
Massachusetts	The following components are listed: Soybean oil
New Jersey	None of the components are listed.
Pennsylvania	The following components are listed: SOYBEAN OIL
California Prop. 65	WARNING: This product contains a chemical known to the State of California to cause cancer. Ethyl acrylate; arsenic; Propylene oxide; 1,4-dioxane
	WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm. 4-methylpentan-2-one; lead; Cadmium (Non-pyrophoric); Ethylene oxide
Other regulations	
Australia inventory (AICS)	All components are listed or exempted.
Canada inventory	All components are listed or exempted.
China inventory (IECSC)	All components are listed or exempted.
Japan inventory (ENCS)	All components are listed or exempted.
Korea inventory (KECI)	All components are listed or exempted.
Philippines inventory (PICCS)	All components are listed or exempted.
Taiwan inventory (CSNN)	Not determined.
REACH Status	For the REACH status of this product please consult your company contact, as identified in Section 1.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

National Fire Protection Association (U.S.A.)

Product name	Molub-Alloy GM 1500		Product code	468757-US69	Page: 8/9
Version 1	Date of issue 03/11/2015.	Format	US	Language	ENGLISH
			(US)		(ENGLISH)

Section 16. Other information



<u>History</u>	
Date of issue/Date of	
revision	
Date of previous issue	
Key to abbreviations	

03/11/2015. No previous validation. ACGIH = American Conference of Industrial Hygienists ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor CAS Number = Chemical Abstracts Service Registry Number GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) OEL = Occupational Exposure Limit SDS = Safety Data Sheet STEL = Short term exposure limit TWA = Time weighted average UN = United Nations UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods.

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name	Molub-Alloy GM 1500	Product code	468757-US69	Page: 9/9
Version 1	Date of issue 03/11/2015.	Format US	Language	ENGLISH
		(US)		(ENGLISH)