



Molub-Alloy™ GM Gear Oil Range

Gear oils

Description

Castrol Molub-Alloy GM™ Gear oils (Previously called Molub-Alloy™ Gear oils) were developed for the lubrication of enclosed gears. They are manufactured from the highest quality components that have been carefully selected for their compatibility with Molub-Alloy GM lubricating solids.

Load carrying capabilities are derived from Molub-Alloy GM's formulation and the proprietary blend of lubricating solids. The lubricating solids are treated to increase their natural affinity for metal surfaces. Also, they are completely dispersed to assure effectiveness over the life of the oil.

Rust and oxidation inhibiting characteristics are maximized to afford effective rust protection and long service life.

Application

Molub-Alloy GM gear oils are recommended for spur, helical, herringbone, and straight or spiral bevel gears. They are especially suited for heavy duty and shock loading where Extreme Pressure (EP) characteristics are required. They should not be used where gear manufacturers specify the use of non-EP lubricants. For severe worm gear service where 'compounded' gear oils are recommended please refer to Molub-Alloy GM 170W/680.

Molub-Alloy GM 300s/1000 is especially suited for service in enclosed gears for heavy-duty industry and mining machinery.

Advantages

- Reduced friction, most evident under boundary conditions, is directly attributed to the presence of specially compounded lubricating solids. This benefit is most pronounced where frequent start-up, slow speeds, and high and unexpected loads are encountered.
- The establishment of a protective layer of Molub-Alloy GM solids provides substantial increase in the working life of both parts and lubricant. This increases load bearing area which can reduce unit pressures operating temperatures, and wear.
- Realistic energy savings are possible through a reduction in peak power demand during cold start-up.
- Seal leakage is greatly reduced. Only compatible base oils that control rubber swelling tendencies are used. The Molub-Alloy GM solids lubricate and improve seal contact surfaces.
- Overall savings are derived from the above and result from less labour and downtime, smoother, more efficient operation with longer parts life, and extended lubrication cycles.

Typical Characteristics

Name	Method	Unit	GM 90/220	GM 690/320	GM 140/460	GM 300s/1000
ISO Viscosity Grade	ASTM D2422	-	220	320	460	1000
AGMA Lubricant Number	-	-	5EP	6EP	7EP	8A EP
Specific gravity @ 60°F	ASTM D 1298	g/cm ³	0.894	0.911	0.900	0.905
Kinematic Viscosity @ 40°C / 104°F	ASTM D445 / ISO 3104	mm ² /s	220	320	460	1000
Kinematic Viscosity @ 100°C / 212°F	ASTM D445	mm ² /s	19.7	25.0	30.6	52.5
Viscosity Index	ASTM D2270	-	102	102	102	100
Flash Point - COC	ASTM D92 / ISO 2592	°C/°F	230	230	240	250
Pour Point	ASTM D97	°C/°F	-18/0	-15/5	-15/5	-9/16
Rust test - Procedure A (24 hrs Distilled Water)	ASTM D665 / ISO 7210	Rating	Pass	Pass	Pass	Pass
Rust test - Procedure B (24 hrs Synthetic Sea Water)	ASTM D665 / ISO 7210	Rating	Pass	Pass	Pass	Pass
FZG Gear Scuffing test - A/8.3/90	DIN 51354	Failure Load Stage	>12	>12	>12	>12
Four Ball Wear test - Wear Scar Diameter (40 kg, 75°C/167°F, 1800 rpm, 1 hr)	ASTM D2266	mm	0.4	0.4	0.4	0.4
Four Ball Weld Load test - Load Wear Index	ASTM D2783	kgf	60	60	62	62
Four Ball Weld Load test - Weld Load	ASTM D2783	kgf	400	400	400	400
Four Ball Wear Test - Scar Diameter	DIN 51350-03-B	mm	<0.40	<0.30	<0.35	<0.40

Subject to usual manufacturing tolerances.

Additional Information

Molub-Alloy GM gear oils cannot be used with diatomaceous earth or any other adsorbent, surface active filter medial.

This product was previously called Molub-Alloy™ Gear oils. The name was changed in 2015.

Molub-Alloy™ GM Gear Oil Range

21 Apr 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial , North America Inc. , 150 West Warrenville Road , 603 1E Naperville , IL 60563

Tel: (877) 641 1600 Fax: (877) 648 9801

www.castrol.com/industrial