

**Product Data** 

## **Performance Biolubes NuCut Plus**

Bio-based Cutting Oil

### **Description**

Castrol Performance Biolubes NuCut Plus is a multi-purpose high performance cutting fluid. Formulated with plant based oils and select additives, it provides lubricity not typically found in conventional mineral based cutting oils. Its natural viscosity index allows this product to maintain viscosity in high temperature operations without the need for additives.

#### **Application**

- · General purpose cutting and grinding
- · Milling, tapping, reaming, gear cutting, broaching, gun drilling and screw machining
- Sharpening high-speed steel and carbide cutting tools

#### **Advantages**

- Improves surface finishes in machining and grinding operations
- Superior lubricity maximizes feed rates and improves productivity
- · Cooler operating temperatures and minimal smoke allow for higher operating speeds
- Minimal mist generation
- · Safe for all metals
- Improves centricity, accuracy and part run-out
- Improves part quality by reducing tool or wheel pressure
- Does not contain chlorine
- · High flash and fire points
- Can be used as a multi-purpose product for cutting and lubrication of the machine

# **Typical Characteristics**

	Test Method	Units	Value
Appearance	Visual	-	Light Yellow Liquid
Viscosity, Kinematic @ 40°C	ASTM D 445	mm²/s	40
Viscosity, Kinematic @ 100°F	ASTM D 445	SUS	195.9
Flash Point, COC	ASTM D 92	°C / °F	282 / 540
4-Ball Wear	ASTM D 4172	mm	0.44
Volatile Organic Compunds	<b>ASTM E 1868</b>	g/L	4

Performance Biolubes NuCut Plus

05 Mar 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial , North America Inc. , 150 West Warrenville Road , 603 1E Naperville , IL 60563 Tel: (877) 641 1600 Fax: (877) 648 9801 www.castrol.com/industrial