



Product Data

Castrol Variocut C 700

High-performance neat cutting oil

Description

Castrol Variocut™ C 700 is a chlorine- and heavy metal-free neat cutting oil.

Application

Variocut C 700 is designed for general machining of ferrous and non-ferrous metals. It is especially suitable for aerospace materials such as titanium, aluminum and high nickel alloys.

	Cast Iron	Low-medium alloyed steel	High alloyed steel/nickel-chromium alloys	Titanium alloys	Aluminum alloys	Yellow metals
Honing/Superfinishing	-	-	-	-	-	-
Grinding	-	-	-	-	-	-
Drilling	-	-	-	✓	✓	✓
Broaching/Gear manufacturing	-	-	-	-	-	-
General machining	✓	✓	✓	✓	✓	✓

Advantages

- Advanced additive technology gives excellent lubricity properties and helps lower production costs through extended tool life
- Improved surface finish and increased cutting speeds help improve process efficiency.
- Multi-metal machining using our superior additive technology provides opportunity for product consolidation
- Our chlorine and heavy-metal free formulation improves the environmental profile and reduces disposal costs
- Low viscosity and excellent wetting characteristics reduces drag-out and can result in reduced product usage.

Typical Characteristics

Properties	Unit	Standard	Data
Appearance	Visual	Visual	Pale yellow
Viscosity @ 40°C	mm ² /s	DIN 51562	11
Viscosity@ 100°F	[SUS]	ASTM D 446	65
Density @ 15°C	kg/m ³	DIN 51757 ASTM D 1298	844
	lbs/gal	Calculated	7.04
Flashpoint COC	°C	ISO 2592	> 170
	°F	ASTM D 92	> 335
Copper corrosion	3 hr at 100°C	ISO 2160 ASTM D 130	1b

	Ester	Active sulphur	Inactive sulphur	Phosphorous	Calcium	Chlorine	Zinc
Additives	+	-	-	+	-	-	-

Castrol Variocut C 700
18/12/2006, version 1.0

Castrol, Variocut and the Castrol logo are trademarks of Castrol Limited, used under license.

All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol Ltd products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product.

Castrol Industrial North America Inc. 150 West Warrenville Road, 605 3E Naperville, IL 60563
Tel: (877) 641 1600 Fax: (877) 648 9801

www.castrol.com/industrial