SAFETY DATA SHEET



Section 1. Identification		
Product name	Braycote 610	
SDS #	451198	
Historic SDS #:	25026	
Code	451198-US03	
Relevant identified uses of	of the substance or mixture and uses advised against	
Product use	Grease for industrial applications For specific application advice see appropriate Technical Data Sheet or consult our company representative.	
Supplier	Castrol Industrial North America, Inc. 150 W. Warrenville Road Naperville, IL 60563 Product Information: +1-877-641-1600	
	BP Lubricants USA Inc. 1500 Valley Road Wayne, NJ 07470 Telephone: (973) 633-2200	
EMERGENCY SPILL INFORMATION:	1 (800) 424-9300 CHEMTREC (USA)	

Section 2. Hazards identification

OSHA/HCS status	This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).	
Classification of the substance or mixture	Not classified.	
GHS label elements		
Signal word	No signal word.	
Hazard statements	No known significant effects or critical hazards.	
Precautionary statements		
Prevention	Not applicable.	
Response	Not applicable.	
Storage	Not applicable.	
Disposal	Not applicable.	
Hazards not otherwise classified	Note: High Pressure Applications Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. See 'Notes to physician' under First-Aid Measures, Section 4 of this Safety Data Sheet.	

Product name Braycote 610	Product code	451198-US03	Page: 1/9
Version 1.02 Date of issue 07/21/2016.	Format US	Language	ENGLISH
	(US)		(ENGLISH)

Section 3. Composition/information on ingredients

Synthetic base stock. Proprietary performance additives.

Substance/mixture

Mixture

Ingredient name	CAS number	%
,	68037-01-4 8012-95-1	≥25 - ≤50 ≤5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention if symptoms occur.
Skin contact	Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.
Inhalation	If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

The exposed person may need to be kept under medical surveillance for 48 hours. Treatment should in general be symptomatic and directed to relieving any effects. Note: High Pressure Applications Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discolored and extremely painful with extensive subcutaneous necrosis. Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimize tissue loss and prevent or limit permanent damage. Note that high pressure may force the product
considerable distances along tissue planes. No specific treatment.

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	In case of fire, use water fog, alcohol resistant foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet.
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst.

Product name	Braycote 610		Product code	451198-US03	Page: 2/9
Version 1.02	Date of issue 07/21/2016.	Format	US	Language	ENGLISH
			(US)		(ENGLISH)

Section 5. Fire-fighting measures

Hazardous combustion products	Combustion products may include the following: carbon dioxide carbon monoxide nitrogen oxides	
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Special protective equipment for fire-fighters	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.	

Section 6. Accidental release measures

Personal precautions, protecti	ve equipment and emergency procedures			
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.			
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".			
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).			
Methods and materials for con	itainment and cleaning up			
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.			
Large spill	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. If emergency personnel are unavailable, contain spilled material. Suction or scoop the spill into appropriate disposal or recycling vessels, then cover spill area with oil absorbent. Dispose of via a licensed waste disposal contractor.			

Section 7. Handling and storage

Precautions for safe handling	
Protective measures	Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Product name	Braycote 610		Product code	451198-US03	Page: 3/9
Version 1.02	Date of issue 07/21/2016.	Format	US	Language	ENGLISH
			(US)		(ENGLISH)

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Pecene, homopolymer, hydrogenated	None.
white mineral oil	ACGIH TLV (United States). TWA: 5 mg/m ³ 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction OSHA PEL (United States). TWA: 5 mg/m ³ 8 hours. Issued/Revised: 6/1993

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

controls	All activities involving chemicals should be assessed exposures are adequately controlled. Personal pro- considered after other forms of control measures (suitably evaluated. Personal protective equipment standards, be suitable for use, be kept in good con Your supplier of personal protective equipment sho selection and appropriate standards. For further in organisation for standards. Provide exhaust ventilation or other engineering co concentrations below their respective occupational The final choice of protective equipment will depen important to ensure that all items of personal prote Emissions from ventilation or work process equipm	tective equipment sho e.g. engineering contri- should conform to ap dition and properly ma ould be consulted for a formation contact you entrols to keep the rele exposure limits. d upon a risk assess ctive equipment are co	uld only be ols) have been propriate aintained. dvice on r national evant airborne nent. It is ompatible.
controls	comply with the requirements of environmental pro fume scrubbers, filters or engineering modifications necessary to reduce emissions to acceptable levels	tection legislation. In s to the process equip	some cases,
Individual protection measures			
	Wash hands, forearms and face thoroughly after he eating, smoking and using the lavatory and at the e Appropriate techniques should be used to remove Wash contaminated clothing before reusing. Ensu showers are close to the workstation location.	end of the working per potentially contaminat	iod. ed clothing.
Eye/face protection	Safety glasses with side shields.		
Skin protection			
	Wear protective gloves if prolonged or repeated co resistant gloves. Recommended: Nitrile gloves. T depends upon the chemicals being handled, the co condition of the gloves (even the best chemically re repeated chemical exposures). Most gloves provide before they must be discarded and replaced. Beca material handling practices vary, safety procedures intended application. Gloves should therefore be cl manufacturer and with a full assessment of the wo	he correct choice of plonditions of work and u esistant glove will breat e only a short time of p ause specific work enveloped should be developed	rotective gloves use, and the ak down after protection vironments and for each
	Consult your supervisor or Standard Operating Pro	ocedure (S.O.P) for sp	ecial handling
Body protection	instructions. Use of protective clothing is good industrial practice Cotton or polyester/cotton overalls will only provide contamination that will not soak through to the skin regular basis. When the risk of skin exposure is hi if there is a risk of splashing) then chemical resista suits and boots will be required. Personal protective equipment for the body should performed and the risks involved and should be ap this product.	protection against lig 0. Overalls should be l gh (e.g. when cleaning nt aprons and/or impe be selected based on	laundered on a g up spillages or ervious chemical the task being
Product name Braycote 610	Product code	451198-US03	Page: 4/9
Version 1.02 Date of issue 07/		Language	-

(US)

(ENGLISH)

Section 8. Exposure controls/personal protection

Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	Grease
Color	Yellow.
Odor	Bland.
Odor threshold	Not available.
рН	Not available.
Melting point	Not available.
Boiling point	Not available.
Flash point	Open cup: 230°C (446°F) [Cleveland.]
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable. Based on - Physical state
Lower and upper explosive (flammable) limits	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Density	<1000 kg/m³ (<1 g/cm³) at 16°C
Solubility	insoluble in water.
Partition coefficient: n- octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.

Section 10. Stability and reactivity

Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not occur.
Conditions to avoid	No specific data.
Incompatible materials	Reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Product name Braycote 610	Product code	451198-US03	Page: 5/9
Version 1.02 Date of issue 07/21/2016.	Format US	Language	ENGLISH
	(US)		(ENGLISH)

Section 11. Toxicological information

Information on toxicological effects

Aspiration hazard

Name	Result
Pecene, homopolymer, hydrogenated	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	Routes of entry anticipated: Dermal, Inhalation.
Potential acute health effects	
Eye contact	No known significant effects or critical hazards.
Skin contact	No known significant effects or critical hazards.
Inhalation	Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Ingestion	No known significant effects or critical hazards.
Symptoms related to the phys	sical, chemical and toxicological characteristics
Eye contact	No specific data.
Skin contact	No specific data.
Inhalation	No specific data.
Ingestion	No specific data.
Delayed and immediate effect	s and also chronic effects from short and long term exposure
Short term exposure	
Potential immediate effects	Not available.
Potential delayed effects	Not available.
Long term exposure	
Potential immediate	Not available.

No known significant effects or critical hazards.

Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

Potential delayed effects

Potential chronic health effects

Not available.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

effects

General

Carcinogenicity

Mutagenicity

Teratogenicity

Product name Braycote 610	Product code	451198-US03	Page: 6/9
Version 1.02 Date of issue 07/21/2016.	Format US	Language	ENGLISH
	(US)		(ENGLISH)

Section 12. Ecological information

Toxicity

No testing has been performed by the manufacturer.

Persistence and degradability

Expected to be biodegradable.

Bioaccumulative potential

Not available.

<u>Mobility in soil</u>	
Soil/water partition coefficient (K _{oc})	Not available.
Mobility	Non-volatile. Grease insoluble in water.

Other adverse effects No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

Special precautions for user Not

Not available.

Not available.

Transport in bulk according to Annex II of MARPOL and the IBC Code

Product nameBraycote 610Version 1.02Date of issue 07/21/2016.

 Product code
 451198-US03
 Page: 7/9

 Format
 US
 Language
 ENGLISH

 (US)
 (ENGLISH)

Section 15. Regulatory information

U.S. Federal regulations United States inventory All components are listed or exempted. (TSCA 8b) SARA 302/304 **Composition/information on ingredients** No products were found. SARA 311/312 Classification Not applicable. **SARA 313** Form R - Reporting This product does not contain any hazardous ingredients at or above regulated thresholds. requirements **Supplier notification** This product does not contain any hazardous ingredients at or above regulated thresholds. State regulations **Massachusetts** The following components are listed: OIL MIST, MINERAL The following components are listed: MINERAL OIL (HIGHLY REFINED); OIL MIST, **New Jersey** MINERAL Pennsylvania The following components are listed: MINERAL OIL MIST California Prop. 65 WARNING: This product contains a chemical known to the State of California to cause cancer. white mineral oil; naphthalene Other regulations Australia inventory (AICS) All components are listed or exempted. **Canada inventory** All components are listed or exempted. China inventory (IECSC) All components are listed or exempted. Japan inventory (ENCS) All components are listed or exempted. Korea inventory (KECI) All components are listed or exempted. **Philippines inventory** All components are listed or exempted. (PICCS) **Taiwan Chemical** All components are listed or exempted. Substances Inventory

The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

Section 16. Other information

National Fire Protection Association (U.S.A.)

(TCSI) REACH Status



<u>History</u>	
Date of issue/Date of revision	07/21/2016.
Date of previous issue	01/21/2016.
Prepared by	Product Stewardship

Product name Braycote 610	Product code	451198-US03	Page: 8/9
Version 1.02 Date of issue 07/21/2016.	Format US	Language	ENGLISH
	(US)		(ENGLISH)

Section 16. Other information

Key to abbreviations	ACGIH = American Conference of Industrial Hygienists
	ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	CAS Number = Chemical Abstracts Service Registry Number
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as
	modified by the Protocol of 1978. ("Marpol" = marine pollution)
	OEL = Occupational Exposure Limit
	SDS = Safety Data Sheet
	STEL = Short term exposure limit
	TWA = Time weighted average
	UN = United Nations
	UN Number = United Nations Number, a four digit number assigned by the United
	Nations Committee of Experts on the Transport of Dangerous Goods.
	Varies = may contain one or more of the following 101316-69-2, 101316-70-5,
	101316-71-6, 101316-72-7, 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4,
	64741-97-5, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7,
	64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-64-9,
	64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1, 74869-22-0, 90669-74-2

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name	Braycote 610		Product code	451198-US03	Page: 9/9
Version 1.02	Date of issue 07/21/2016.	Format	US	Language	ENGLISH
			(US)		(ENGLISH)