



GTX Magnatec 5W-30

CLINGING MOLECULES PROTECT FROM THE START

Description

Did you know testing confirms that up to 75% of engine wear occurs during the first 20 minutes of warm up?*

When your engine stops, oil drains off critical engine parts, but Castrol GTX MAGNATEC's intelligent molecules don't – they form an extra layer of protection during warm up, when your engine needs it most, dramatically reducing engine wear and keeping critical parts up to 4X smoother.*

* As tested in the industry Sequence IVA wear test.

Castrol GTX MAGNATEC also delivers:

- Superior wear protection on critical engine parts
- Unsurpassed level of protection against viscosity breakdown
- Unique synthetic technology to fight against harmful sludge build-up
- High level of fuel economy based on US industry standards

Application

Industry Specifications and OEM Approvals:

* API SN

* ILSAC GF-5

* dexos1®

* Meets Ford WSS M2C929-A and Ford WSS M2C946-A

* Meets engine test requirements of Chrysler MS 6395

dexos1® is a registered trademark of General Motors

Typical Physical Characteristics

Castrol GTX Magnatec 5W-30

	Method	Result
Viscosity @ 100C, cSt	ASTM D455	11.20 cSt
Viscosity @ 40C, cSt	ASTM D455	68.6 cSt
Viscosity Index	ASTM D2270	156
Low temperature (C) Cranking viscosity, cP max	ASTM D5293	6600 max
Low temperature (C) Pumping viscosity, cP max	ASTM D4684	40000 max
HT/HS viscosity, cP min	ASTM D4683	2.9 min
Pour Point (C), max	ASTM D97	-36 max
Flash Point PMCC C, min	ASTM D93	200 C min
Density	ASTM D4052	0.860

Due to continual product research and development, the information contained herein is based on products purchased and subject to change without notification.

Typical properties may vary slightly.

Concentration Control

Based on available information, this product is not expected to produce adverse effect on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office or via the Internet at www.castrol.com/us. This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment; return used oil to collection center.

GTX Magnatec 5W-30

27 Feb 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470

Telephone: 1,800.462.0835

www.castrol.com/us Email: contactus@bp.com