



Product Data

Castrol Honilo 980

High-performance neat cutting oil

Description

Castrol Honilo™ 980 is a chlorine-free low viscosity neat cutting oil, which is sulphur- and heavy metal-free.

Application

Honilo 980 has been designed for honing and superfinishing of ferrous and non-ferrous materials. It can also be used for grinding applications, drilling and general machining of aluminum and yellow metals.

	Cast Iron	Low-medium alloyed steel	High alloyed steel/ nickel-chromium alloys	Titanium alloys	Aluminum alloys	Yellow metals
Honing/Superfinishing	✓	✓	✓	-	✓	✓
Grinding	✓	✓	✓	-	✓	✓
Drilling	-	-	-	-	✓	✓
Broaching/Gear manufacturing	-	-	-	-	-	-
General machining	-	-	-	-	-	✓

Advantages

- Excellent flushing and lubrication properties extend honing stone life and enable high surface finish and dimensional accuracy.
- Low viscosity and excellent wetting properties reduces drag-out and can result in lower product usage.
- Good filtering characteristics and high oxidation stability help increase product lifetime.
- Our chlorine- and heavy metal-free formulation improves the environmental profile and reduces disposal costs.
- Low odor, light color and low mist aid in operator acceptability.

Typical Characteristics

Properties	Unit	Standard	Data
Appearance	Visual	Visual	Yellow
Viscosity @ 40°C	mm ² /s	DIN 51562	4.5
Viscosity@ 100°F	[SUS]	ASTM D 446	45
Density @ 15°C	kg/m ³	DIN 51757 ASTM D 1298	824
	lbs/gal	Calculated	6.88
Flashpoint COC	°C	ISO 2592	> 112
	°F	ASTM D 92	> 235
Copper corrosion	3 hr at 100°C	ISO 2160 ASTM D 130	1b

	Ester	Active sulphur	Inactive sulphur	Phosphorous	Calcium	Chlorine	Zinc
Additives	+	-	-	+	-	-	-

Castrol Honilo 980

18/12/2006, version 1.0

Castrol, Honilo and the Castrol logo are trademarks of Castrol Limited, used under license.

All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol Ltd products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product.

Castrol Industrial North America Inc. 150 West Warrenville Road, 605 3E Naperville, IL 60563
Tel: (877) 641 1600 Fax: (877) 648 9801

www.castrol.com/industrial