# SAFETY DATA SHEET



#### **Section 1. Identification** lloform FST 14 **Product name** 459498 SDS# Historic SDS #: 08133 459498-US03 Code Relevant identified uses of the substance or mixture and uses advised against Product use Metalworking fluid - neat. For specific application advice see appropriate Technical Data Sheet or consult our company representative. Supplier Castrol Industrial North America, Inc. 150 W. Warrenville Road Naperville, IL 60563 Product Information: +1-877-641-1600 BP Lubricants USA Inc. 1500 Valley Road Wayne, NJ 07470 Telephone: (973) 633-2200 1 (800) 424-9300 CHEMTREC (USA) **EMERGENCY SPILL**

#### INFORMATION:

## Section 2. Hazards identification

OSHA/HCS status       This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).         Classification of the substance or mixture       Not classified.		
		GHS label elements
Signal word	No signal word.	
Hazard statements	No known significant effects or critical hazards.	
Precautionary statements		
Prevention	Not applicable.	
Response	Not applicable.	
Storage	Not applicable.	
Disposal	Not applicable.	
Hazards not otherwise classified	Defatting to the skin.	

## Section 3. Composition/information on ingredients

Highly refined base oil and additives.

Substance/mixture

Mixture

Product name	lloform FST 14		Product code	459498-US03	Page: 1/9
Version 3	Date of issue 08/03/2016.	Format	US	Language	ENGLISH
			(US)		(ENGLISH)

# Section 3. Composition/information on ingredients

Ingredient name	CAS number	%
Sistillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	≥25 - ≤50
Base oil - highly refined	Varies - See Key to abbreviations	≥25 - ≤50
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	68584-23-6	≤5
Sulfonic acids, petroleum, calcium salts	61789-86-4	≤2.4
Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts	70024-69-0	≤2.4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.

### Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects.
Specific treatments	No specific treatment.

## Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet.
Specific hazards arising from the chemical Swarf fires - Neat metal working oils may fume, thermally decompose or ignite if come into contact with red hot swarf. To minimise the generation of red hot swarf that a sufficient flow of oil is correctly directed to the cutting edge of the tool to flo throughout cutting operations. As an additional precaution swarf should be regula cleared from the immediate area to prevent the risk of fire. In a fire or if heated, a pressure increase will occur and the container may burst.	
Hazardous combustion products	Combustion products may include the following: carbon dioxide carbon monoxide sulfur oxides
Special protective actions for fire-fightersPromptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Product name Iloform FST 1	4 <b>Product code</b> 459498-US03 <b>Page: 2/9</b>
Version 3 Date of issue	08/03/2016. Format US Language ENGLISH

(US)

(ENGLISH)

## Section 5. Fire-fighting measures

Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

### Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures				
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.			
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".			
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).			
Methods and materials for con	tainment and cleaning up			
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.			
Large spill	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.			

### Section 7. Handling and storage

#### Precautions for safe handling Protective measures Put on appropriate personal protective equipment (see Section 8). Concentrations of mist, fumes and vapors in enclosed spaces may result in the formation of explosive atmospheres. Excessive splashing, agitation or heating must be avoided. During metal working, solid particles from workpieces or tools will contaminate the fluid and may cause abrasions of the skin. Where such abrasions result in a penetration of the skin, first aid treatment should be applied as soon as reasonably possible. The presence of certain metals in the workpiece or tool, such as chromium, cobalt and nickel, can contaminate the metalworking fluid, as can bacteria, and as a result may induce allergic and other skin reactions, especially if personal hygiene is inadequate. Eating, drinking and smoking should be prohibited in areas where this material is Advice on general handled, stored and processed. Wash thoroughly after handling. Remove contaminated occupational hygiene clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. Conditions for safe storage, Store in accordance with local regulations. Store in original container protected from including any direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until incompatibilities ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Sulfur compounds in this material may decompose when heated to release hydrogen sulfide gas which may accumulate to potentially lethal concentrations in enclosed air spaces. Vapor concentrations of hydrogen sulfide above 50 ppm, or prolonged exposure at lower concentrations, may saturate human odor perceptions so that the smell of gas may not be apparent. Exposure to concentrations of hydrogen sulfide vapor above 500 ppm may cause rapid death. Do not rely on the sense of smell to detect hydrogen sulfide.

Product name	lloform FST 14		Product code	459498-US03	Page: 3/9
Version 3	Date of issue 08/03/2016.	Format	US	Language	ENGLISH
			(US)		(ENGLISH)

## Section 8. Exposure controls/personal protection

**Control parameters Occupational exposure limits** Distillates (petroleum), hydrotreated heavy paraffinic ACGIH TLV (United States). TWA: 5 mg/m<sup>3</sup> 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction **OSHA PEL (United States).** TWA: 5 mg/m<sup>3</sup> 8 hours. Issued/Revised: 6/1993 Base oil - highly refined ACGIH TLV (United States). TWA: 5 mg/m<sup>3</sup> 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction **OSHA PEL (United States).** TWA: 5 mg/m<sup>3</sup> 8 hours. Issued/Revised: 6/1993 Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts None. Sulfonic acids, petroleum, calcium salts None. Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts None. Appropriate engineering All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be controls considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible. Emissions from ventilation or work process equipment should be checked to ensure they **Environmental exposure** comply with the requirements of environmental protection legislation. In some cases, controls fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Individual protection measures **Hygiene measures** Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Eye/face protection Safety glasses with side shields. **Skin protection** Hand protection Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after

intended application. Gloves should therefore be chosen in consultation with the supplier/ manufacturer and with a full assessment of the working conditions. Consult your supervisor or Standard Operating Procedure (S.O.P) for special handling instructions.

repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each

Product name	lloform FST 14		Product code	459498-US03	Page: 4/9
Version 3	Date of issue 08/03/2016.	Format	US	Language	ENGLISH
			(US)		(ENGLISH)

# Section 8. Exposure controls/personal protection

Body protection	Use of protective clothing is good industrial practice. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

# Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	Liquid.
Color	Amber.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point	Not available.
Boiling point	Not available.
Flash point	Closed cup: 162.5°C (324.5°F) [Pensky-Martens.]
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable. Based on - Physical state
Lower and upper explosive (flammable) limits	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Density	✓1000 kg/m³ (<1 g/cm³) at 15.6°C
Solubility	insoluble in water.
Partition coefficient: n- octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Kīnematic: 86 mm²/s (86 cSt) at 40°C

# Section 10. Stability and reactivity

Reactivity	No specific test data available for this product. Refer to Conditions to avoid and ncompatible materials for additional information.		
Chemical stability	The product is stable.		
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not occur.		
Conditions to avoid	Avoid excessive heat.		
Product name Iloform FST 14	Product code 459498-US03 Page: 5/9		
Version 3 Date of issue 0	8/03/2016. Format US Language ENGLISH		

(US)

(ENGLISH)

### Section 10. Stability and reactivity

Incompatible materials

Reactive or incompatible with the following materials: oxidizing materials.

Hazardous decomposition products

Hydrogen Sulfide (H2S)

## Section 11. Toxicological information

#### Information on toxicological effects **Aspiration hazard** Name Result Distillates (petroleum), hydrotreated heavy paraffinic ASPIRATION HAZARD - Category 1 Information on the likely Routes of entry anticipated: Dermal, Inhalation. routes of exposure Potential acute health effects Eye contact No known significant effects or critical hazards. Skin contact No known significant effects or critical hazards. Inhalation Vapor inhalation under ambient conditions is not normally a problem due to low vapor pressure. Ingestion No known significant effects or critical hazards. Symptoms related to the physical, chemical and toxicological characteristics Eye contact No specific data. Skin contact Adverse symptoms may include the following: irritation dryness cracking Inhalation No specific data. Ingestion No specific data. Delayed and immediate effects and also chronic effects from short and long term exposure Short term exposure Potential immediate Not available. effects **Potential delayed effects** Not available. Long term exposure **Potential immediate** Not available. effects **Potential delayed effects** Not available. Potential chronic health effects General No known significant effects or critical hazards. Carcinogenicity No known significant effects or critical hazards. **Mutagenicity** No known significant effects or critical hazards. Teratogenicity No known significant effects or critical hazards. **Developmental effects** No known significant effects or critical hazards. **Fertility effects** No known significant effects or critical hazards.

### Numerical measures of toxicity

Acute toxicity estimates

Not available.

Product name	lloform FST 14		Product code	459498-US03	Page: 6/9
Version 3	Date of issue 08/03/2016.	Format	US	Language	ENGLISH
			(US)		(ENGLISH)

## Section 12. Ecological information

### **Toxicity**

No testing has been performed by the manufacturer.

### Persistence and degradability

Expected to be biodegradable.

### **Bioaccumulative potential**

Not available.

<u>Mobility in soil</u>	
Soil/water partition coefficient (Koc)	Not available.
Mobility	Non-volatile. Liquid. insoluble in water.

Other adverse effects No known significant effects or critical hazards.

## Section 13. Disposal considerations

Disposal methods The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information					
	DOT Classification	TDG Classification	IMDG	ΙΑΤΑ	
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	
UN proper shipping name	-	-	-	-	
Transport hazard class(es)	-	-	-	-	
Packing group	-	-	-	-	
Environmental hazards	No.	No.	No.	No.	
Additional information	-	-	-	-	

Special precautions for user Not available.

 Product name
 Iloform FST 14
 Product code
 459498-US03
 Page: 7/9

 Version 3
 Date of issue 08/03/2016.
 Format US
 Language
 ENGLISH

 (US)
 (ENGLISH)

# Section 14. Transport information

Transport in bulk according Not available. to Annex II of MARPOL and the IBC Code

# Section 15. Regulatory information

U.S. Federal regulations	
United States inventory (TSCA 8b)	All components are listed or exempted.
SARA 302/304	
Composition/information	on ingredients
No products were found.	
SARA 311/312	
Classification	Not applicable.
<u>SARA 313</u>	
Form R - Reporting requirements	This product does not contain any hazardous ingredients at or above regulated thresholds.
Supplier notification	This product does not contain any hazardous ingredients at or above regulated thresholds.
State regulations	
Massachusetts	The following components are listed: OIL MIST, MINERAL; OIL MIST, MINERAL; Fatty acids, vegetable-oil, Me esters, sulfurized; Rape oil, sulfurized
New Jersey	The following components are listed: MINERAL OIL (UNTREATED and MILDLY TREATED); MINERAL OIL (UNTREATED and MILDLY TREATED); Calcium sulfonate or oil soluble calcium sulfonate; Fatty acids, vegetable-oil, Me esters, sulfurized; Rape oil, sulfurized
Pennsylvania	The following components are listed: MINERAL OIL MIST; MINERAL OIL MIST; Fatty acids, vegetable-oil, Me esters, sulfurized; Rape oil, sulfurized
California Prop. 65	No products were found.
Other regulations	
Australia inventory (AICS)	At least one component is not listed.
Canada inventory	All components are listed or exempted.
China inventory (IECSC)	All components are listed or exempted.
Japan inventory (ENCS)	All components are listed or exempted.
Korea inventory (KECI)	All components are listed or exempted.
Philippines inventory (PICCS)	All components are listed or exempted.
Taiwan Chemical Substances Inventory (TCSI)	Not determined.
REACH Status	For the REACH status of this product please consult your company contact, as identified in Section 1.

## Section 16. Other information





### **History**

Date of issue/Date of revision

08/03/2016.

Product name	lloform FST 14		Product code	459498-US03	Page: 8/9
Version 3	Date of issue 08/03/2016.	Format	US	Language	ENGLISH
			(US)		(ENGLISH)

## Section 16. Other information

Date of previous issue	03/31/2016.
Prepared by	Product Stewardship
Key to abbreviations	ACGIH = American Conference of Industrial Hygienists ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor CAS Number = Chemical Abstracts Service Registry Number GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) OEL = Occupational Exposure Limit SDS = Safety Data Sheet STEL = Short term exposure limit TWA = Time weighted average UN = United Nations UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods. Varies = may contain one or more of the following 101316-69-2, 101316-70-5, 101316-71-6, 101316-72-7, 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64741-97-5, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7,
	64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-64-9, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1, 74869-22-0, 90669-74-2
	0+1+2-05-0, 0+1+2-10-1, 12020-05-0, 12020-06-0, 12020-01-1, 1+000-22-0, 500005-1+-2

Indicates information that has changed from previously issued version.

### Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name	lloform FST 14		Product code	459498-US03	Page: 9/9
Version 3	Date of issue 08/03/2016.	Format	US	Language	ENGLISH
			(US)		(ENGLISH)