

## Section 1. Identification

**Product name** Techniclean 2000  
**SDS #** 459539  
**Historic SDS #:** 11111  
**Code** 459539-US03

### Relevant identified uses of the substance or mixture and uses advised against

**Product use** Cleaner.  
 For specific application advice see appropriate Technical Data Sheet or consult our company representative.

**Manufacturer** Castrol Industrial North America, Inc.  
 150 W. Warrenville Road  
 Naperville, IL 60563

**Supplier** Castrol Industrial North America, Inc.  
 150 W. Warrenville Road  
 Naperville, IL 60563  
 Product Information: +1-877-641-1600

**EMERGENCY SPILL INFORMATION:** 1 (800) 424-9300 CHEMTREC (USA)

## Section 2. Hazards identification

**OSHA/HCS status** This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Classification of the substance or mixture** SKIN CORROSION/IRRITATION - Category 2  
 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

### GHS label elements

#### Hazard pictograms



**Signal word** Danger

**Hazard statements** Causes serious eye damage.  
 Causes skin irritation.

### Precautionary statements

**Prevention** Wear protective gloves. Wear eye or face protection. Wash hands thoroughly after handling.

**Response** IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.

**Storage** Not applicable.

**Disposal** Not applicable.

**Hazards not otherwise classified** Defatting to the skin.

<b>Product name</b> Techniclean 2000	<b>Product code</b> 459539-US03	<b>Page:</b> 1/10
<b>Version</b> 1.01 <b>Date of issue</b> 08/18/2014.	<b>Format</b> US (US)	<b>Language</b> ENGLISH (ENGLISH)

## Section 3. Composition/information on ingredients

Alkalis and additives in aqueous solution.

**Substance/mixture** Mixture

Ingredient name	CAS number	%
diphosphoric acid, tetrapotassium salt	7320-34-5	5-10
alcohols, C9-11, ethoxylated	68439-46-3	1-5
poly(oxy-1,2-ethanediyl), $\alpha$ -[(1,1,3,3-tetramethylbutyl)phenyl]- $\omega$ -hydroxy-, phosphate	52623-95-7	1-5
dipropylene glycol methyl ether	34590-94-8	0.1-1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

<b>Eye contact</b>	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Chemical burns must be treated promptly by a physician. Get medical attention immediately.
<b>Skin contact</b>	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
<b>Inhalation</b>	If inhaled, remove to fresh air. Get medical attention immediately.
<b>Ingestion</b>	Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Chemical burns must be treated promptly by a physician. Wash out mouth with water if person is conscious. Get medical attention immediately.
<b>Protection of first-aiders</b>	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

### Indication of immediate medical attention and special treatment needed, if necessary

<b>Notes to physician</b>	Treatment should in general be symptomatic and directed to relieving any effects.
<b>Specific treatments</b>	No specific treatment.

## Section 5. Fire-fighting measures

### Extinguishing media

<b>Suitable extinguishing media</b>	In case of fire, use water fog, alcohol resistant foam, dry chemical or carbon dioxide extinguisher or spray.
<b>Unsuitable extinguishing media</b>	Do not use water jet.

**Specific hazards arising from the chemical** In a fire or if heated, a pressure increase will occur and the container may burst.

<b>Product name</b> Techniclean 2000	<b>Product code</b> 459539-US03	<b>Page:</b> 2/10
<b>Version</b> 1.01 <b>Date of issue</b> 08/18/2014.	<b>Format</b> US (US)	<b>Language</b> ENGLISH (ENGLISH)

## Section 5. Fire-fighting measures

<b>Hazardous combustion products</b>	Combustion products may include the following: carbon dioxide carbon monoxide phosphorus oxides metal oxide/oxides
<b>Special protective actions for fire-fighters</b>	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
<b>Special protective equipment for fire-fighters</b>	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

<b>For non-emergency personnel</b>	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling. Contact emergency personnel.
<b>For emergency responders</b>	Entry into a confined space or poorly ventilated area contaminated with vapor, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".
<b>Environmental precautions</b>	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

<b>Small spill</b>	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
<b>Large spill</b>	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilled product. Dispose of via a licensed waste disposal contractor.

## Section 7. Handling and storage

### Precautions for safe handling

<b>Protective measures</b>	Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Avoid contact of spilled material and runoff with soil and surface waterways. Do not ingest. Empty containers retain product residue and can be hazardous. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Do not breathe vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Use only with adequate ventilation.
<b>Advice on general occupational hygiene</b>	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

<b>Product name</b> Techniclean 2000	<b>Product code</b> 459539-US03	<b>Page:</b> 3/10
<b>Version</b> 1.01 <b>Date of issue</b> 08/18/2014.	<b>Format</b> US (US)	<b>Language</b> ENGLISH (ENGLISH)

## Section 7. Handling and storage

### Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
dipropylene glycol methyl ether	<p><b>ACGIH TLV (United States). Absorbed through skin.</b> STEL: 909 mg/m<sup>3</sup> 15 minutes. Issued/Revised: 9/1994 STEL: 150 ppm 15 minutes. Issued/Revised: 9/1994 TWA: 606 mg/m<sup>3</sup> 8 hours. Issued/Revised: 9/1994 TWA: 100 ppm 8 hours. Issued/Revised: 9/1994</p> <p><b>OSHA PEL (United States). Absorbed through skin.</b> TWA: 600 mg/m<sup>3</sup> 8 hours. Issued/Revised: 6/1993 TWA: 100 ppm 8 hours. Issued/Revised: 6/1993</p> <p><b>NIOSH REL (United States). Absorbed through skin.</b> TWA: 100 ppm 10 hours. Issued/Revised: 6/1994 TWA: 600 mg/m<sup>3</sup> 10 hours. Issued/Revised: 6/1994 STEL: 150 ppm 15 minutes. Issued/Revised: 6/1994 STEL: 900 mg/m<sup>3</sup> 15 minutes. Issued/Revised: 6/1994</p>

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

### Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**Product name** Techniclean 2000

**Product code** 459539-US03

**Page:** 4/10

**Version** 1.01 **Date of issue** 08/18/2014.

**Format** US  
(US)

**Language** ENGLISH  
(ENGLISH)

## Section 8. Exposure controls/personal protection

### Individual protection measures

#### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

Chemical splash goggles.

#### Skin protection

##### Hand protection

Wear chemical resistant gloves. Recommended: Butyl gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Consult your supervisor or Standard Operating Procedure (S.O.P) for special handling instructions.

##### Body protection

Use of protective clothing is good industrial practice. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

##### Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

##### Respiratory protection

Use with adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory equipment.

Recommended: half-face mask - inorganic gases/vapor filter (Type B) - particulate filter. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

## Section 9. Physical and chemical properties

### Appearance

Physical state	Liquid.
Color	Clear
Odor	Fruity.
Odor threshold	Not available.
pH	8.75 [Conc. (% w/w): 5%]
Melting point	Not available.
Boiling point	Not available.
Flash point	Closed cup: >100°C (>212°F) [Estimated. Water content interferes with flash point determination.]
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable. Based on - Physical state
Lower and upper explosive (flammable) limits	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Density	>1000 kg/m <sup>3</sup> (>1 g/cm <sup>3</sup> ) at 15.6°C

Product name	Techniclean 2000	Product code	459539-US03	Page: 5/10
Version	1.01	Date of issue	08/18/2014.	Format US
				(US)
				Language ENGLISH
				(ENGLISH)

## Section 9. Physical and chemical properties

<b>Solubility</b>	Soluble in water.
<b>Partition coefficient: n-octanol/water</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.

## Section 10. Stability and reactivity

<b>Reactivity</b>	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
<b>Chemical stability</b>	The product is stable.
<b>Possibility of hazardous reactions</b>	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not occur.
<b>Conditions to avoid</b>	High temperatures
<b>Incompatible materials</b>	Reactive or incompatible with the following materials: oxidizing materials.
<b>Hazardous decomposition products</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Specific target organ toxicity (single exposure)

<b>Name</b>	<b>Category</b>	<b>Route of exposure</b>	<b>Target organs</b>
dipropylene glycol methyl ether	Category 3	Not applicable.	Respiratory tract irritation

**Information on the likely routes of exposure** Routes of entry anticipated: Dermal, Inhalation.

#### Potential acute health effects

<b>Eye contact</b>	Causes serious eye damage.
<b>Skin contact</b>	Causes skin irritation.
<b>Inhalation</b>	May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system. May cause irritation to eyes, nose and throat due to exposure to vapor, mists or fumes.
<b>Ingestion</b>	May cause burns to mouth, throat and stomach.

#### Symptoms related to the physical, chemical and toxicological characteristics

<b>Eye contact</b>	Adverse symptoms may include the following: pain watering redness
<b>Skin contact</b>	Adverse symptoms may include the following: irritation redness dryness cracking
<b>Inhalation</b>	No specific data.

<b>Product name</b> Techniclean 2000	<b>Product code</b> 459539-US03	<b>Page:</b> 6/10
<b>Version</b> 1.01 <b>Date of issue</b> 08/18/2014.	<b>Format</b> US (US)	<b>Language</b> ENGLISH (ENGLISH)

## Section 11. Toxicological information

**Ingestion** Adverse symptoms may include the following:  
stomach pains

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

**Potential immediate effects** Not available.

**Potential delayed effects** Not available.

#### Long term exposure

**Potential immediate effects** Not available.

**Potential delayed effects** Not available.

#### Potential chronic health effects

**General** No known significant effects or critical hazards.

**Carcinogenicity** No known significant effects or critical hazards.

**Mutagenicity** No known significant effects or critical hazards.

**Teratogenicity** No known significant effects or critical hazards.

**Developmental effects** No known significant effects or critical hazards.

**Fertility effects** No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Oral	46666.7 mg/kg

## Section 12. Ecological information

### Toxicity

No testing has been performed by the manufacturer.

### Persistence and degradability

Expected to be biodegradable.

### Bioaccumulative potential

Not available.

### Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** Not available.

**Mobility** Liquid. Soluble in water.

### Other adverse effects

No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods**      The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	<b>DOT Classification</b>	<b>TDG Classification</b>	<b>IMDG</b>	<b>IATA</b>
<b>UN number</b>	Not regulated.	Not regulated.	Not regulated.	Not regulated.
<b>UN proper shipping name</b>		-	-	-
<b>Transport hazard class(es)</b>	-	-	-	-
<b>Packing group</b>	-	-	-	-
<b>Environmental hazards</b>	No.	No.	No.	No.
<b>Additional information</b>	-	-	-	-

**Special precautions for user**      Not available.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**      Not available.

## Section 15. Regulatory information

**U.S. Federal regulations**

**United States inventory (TSCA 8b)**      All components are listed or exempted.

**TSCA 12(b) one-time export:** dipropylene glycol methyl ether

**SARA 302/304**

**Composition/information on ingredients**

No products were found.

**SARA 311/312**

**Classification**      Immediate (acute) health hazard

**SARA 313**

**Form R - Reporting requirements**      This product does not contain any hazardous ingredients at or above regulated thresholds.

**Supplier notification**      This product does not contain any hazardous ingredients at or above regulated thresholds.



## Section 15. Regulatory information

### State regulations

#### Massachusetts

The following components are listed: DIPROPYLENE GLYCOL METHYL ETHER

#### New Jersey

The following components are listed: DIPROPYLENE GLYCOL METHYL ETHER;  
(2-METHOXYMETHYLETHOXY) PROPANOL

#### Pennsylvania

The following components are listed: PROPANOL, (2-METHOXYMETHYLETHOXY)-

#### California Prop. 65

**WARNING:** This product contains a chemical known to the State of California to cause cancer.  
1,4-dioxane

### Other regulations

#### Australia inventory (AICS)

All components are listed or exempted.

#### Canada inventory

All components are listed or exempted.

#### China inventory (IECSC)

All components are listed or exempted.

#### Japan inventory (ENCS)

All components are listed or exempted.

#### Korea inventory (KECI)

At least one component is not listed.

#### Philippines inventory (PICCS)

All components are listed or exempted.

#### REACH Status

The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

## Section 16. Other information

### Hazardous Material Information System (U.S.A.)

Health	3
Flammability	1
Physical hazards	0
Personal protection	X

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

### National Fire Protection Association (U.S.A.)



### History

Date of issue/Date of revision 08/18/2014.

Date of previous issue 08/18/2014.

### Key to abbreviations

ACGIH = American Conference of Industrial Hygienists  
ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
CAS Number = Chemical Abstracts Service Registry Number  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
OEL = Occupational Exposure Limit  
SDS = Safety Data Sheet  
STEL = Short term exposure limit  
TWA = Time weighted average

Product name	Techniclean 2000	Product code	459539-US03	Page:	9/10
Version	1.01	Date of issue	08/18/2014.	Format	US (US)
				Language	ENGLISH (ENGLISH)

## Section 16. Other information

UN = United Nations

UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods.

✔ Indicates information that has changed from previously issued version.

### [Notice to reader](#)

*All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.*

*The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.*

*It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.*

**Product name** Techniclean 2000

**Product code** 459539-US03

**Page:** 10/10

**Version** 1.01 **Date of issue** 08/18/2014.

**Format** US  
(US)

**Language** ENGLISH  
(ENGLISH)