



Castrol Transmax CVT

CVT Fluid

Description

Castrol Transmax CVT, formulated with *Smooth Drive Technology*TM and premium full-synthetic base oil, is designed for most continuously variable transmissions. Its superior technology enables longer transmission life. It is suitable for use in most passenger cars fitted with push belt transmissions. Ensuring peace of mind across a wide range of vehicles.

Advantages

- Enhanced friction durability for a smoother drive for longer transmission life.
- Enhanced wear protection for longer transmission life.
- Superior high temperature protection to effectively resist oxidation.
- Superior variator torque capacity that can prevent belt or chain slippage.

Typical Characteristics

Name	Method	Units	Transmax CVT
Density @ 15C, Relative	ASTM D4052	g/ml	0.850
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	35
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	7.25
Viscosity Index	ASTM D2270	None	178
Pour Point	ASTM D97	°C	-51
Viscosity, Brookfield @ -40C	ASTM D2983	mPa.s (cP)	11100
Flash Point, COC	ASTM D92	°C	218

Product Performance Claims

Suitable for use where:

Toyota CVT Fluid TC
Toyota CVT Fluid FE
Nissan CVT Fluid NS-1
Nissan CVT Fluid NS-2
Nissan CVT Fluid NS-3
MMC DIAQUEEN ATF SP-III
MMC DIAQUEEN CVT Fluid J1
MMC DIAQUEEN CVT Fluid J4
Mazda CVTF 3320
Subaru i-CVT Fluid
Subaru i-CVT FG
Subaru Lineartronic High Torque Chain CVTF
Daihatsu AMMIX CVT Fluid DC
Daihatsu AMMIX CVT Fluid DFE
Suzuki CVT Fluid 3320
Suzuki CVT Fluid Green 1
Suzuki CVT Fluid Green 2
Suzuki CVTF TC
Suzuki NS-2
Honda HCF-2
Hyundai/Kia SP-III
Chrysler NS-2
Chrysler CVTF+4
Mini Cooper EZL799
Ford CVT23
MB 236.20

Castrol Transmax CVT

05 Dec 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470

Telephone: 1,800.462.0835

www.castrol.com/us Email: contactus@bp.com