



## Castrol Transmax DEXRON®-VI MERCON® LV

Automatic Transmission Fluid

### Description

Castrol Transmax DEXRON®-VI MERCON® LV Automatic Transmission Fluid is a technologically advanced, low viscosity formulation specially designed to deliver performance and maximum fuel efficiency for modern automatic transmissions and is also suitable for use in some power steering systems. It is blended with premium base stocks, a balanced additive package and is fully approved by both Ford and GM for use in vehicles requiring their latest ATF specifications. In addition to approval from the two major US auto manufacturers, Transmax DEXRON®-VI MERCON® LV ATF exceeds the requirements of the JASO-1A performance standard created by Japanese automobile manufacturers. This standard is recognized by Japanese OEM's in certifying ATF for use in their vehicles.

### Advantages

- OEM approved and licensed by Ford (MERCON® LV) and GM (DEXRON®-VI)
- Low viscosity formula for maximum fuel efficiency in modern automatic transmissions
- Enhanced friction durability for smooth transmission performance
- Superior high temperature protection to effectively resist oxidation
- Unsurpassed protection against copper corrosion

### Typical Characteristics

Name	Method	Units	Transmax DEXRON®-VI MERCON® LV
Density @ 15C, Relative	ASTM D4052	g/ml	0.841
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	5.9
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	30
Viscosity Index	ASTM D2270	None	161
Viscosity, Brookfield @ -40C (75W)	ASTM D2983	mPa.s (cP)	10000
Pour Point	ASTM D97	°C	-54

## Product Performance Claims

MERCON® LV

DEXRON® -VI

JASO 1A, JASO 1A LV

Recommended for use where:

- Toyota T, T II, T III, T IV, WS
- Nissan Matic D, J, S
- Mitsubishi SP II, IIM, III, PA, J3, SP IV
- Mazda ATF M-III, M-V, JWS 3317, FZ
- Subaru F6, Red 1
- Daihatsu AMMIX ATF D-III Multi, D3-SP
- Suzuki AT Oil 5D06, 2384K, JWS 3314, JWS 3317
- Hyundai/Kia SP III, SP IV
- Aisin Transmissions requiring JWS 3309
- Honda/Acura DW 1/Z 1
- Isuzu (where Toyota T-IV is required)  
is required.

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Transmax DEXRON®-VI MERCON® LV

02 Jun 2016

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

[www.castrol.com](http://www.castrol.com)