



Mobil DTE Oil 205
Mobil Industrial, United States

Compressor Oil

Product Description

Mobil DTE Oil 205 is a lubricating oil formulated to provide excellent anti-wear and friction-reducing properties for compressor cylinder lubrication as well as protection against rust and corrosion. Mobil DTE Oil 205 is designed for wet-gas compression and exhibits excellent resistance to washing by water and other entrained liquids. It resists oxidation and provides effective lubrication at low feed rates, thereby extending operating periods between valve-cleaning intervals.

Features and Benefits

Mobil DTE Oil 205 offers the following benefits:

Features	Advantages and Potential Benefits
Excellent resistance to washing by water and other entrained liquids	Extended cylinder, ring, and packing life
Effective lubrication at low feed rates	Reduced oil purchases, extended valve rebuild intervals
Good anti-wear and friction reducing	Extended ring and packing life properties
Rust and corrosion protection	Extended compressor cylinder life
Resists oxidation	Reduced discharge valve deposits, extended valve rebuild intervals

Applications

Mobil DTE Oil 205 lubricant is recommended for the cylinder lubrication of reciprocating compressors and special rotary sliding vane compressors in air and inert gas service. It is particularly applicable where wet gas is being compressed. While developed primarily for multistage compressors, its superior qualities will provide benefits in many single- and two-stage compressors operating at higher pressures or discharge temperatures or when compressing wet gas.

Mobil DTE Oil 205 is not designed for use in compressor crankcases, particularly those compressors having high lead bearings, or crankshafts fitted with lead counterweights.

It should not be used when compressing air for breathing.

Typical Properties

Mobil DTE Oil 205	
Specific Gravity, calc.	0.90
Pour Point, °C (°F)	-9 (16)
Flash Point, °C (°F), min	282(540)
Viscosity, ASTM D 445	
cSt at 40°C	220
cSt at 100°C	19.5

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet at <http://www.msds.exxonmobil.com>. This product should not be used for purposes other than its intended use. If disposing used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and DTE are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

Exxon Mobil Corporation
22777 Springwoods Village Parkway
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil,

or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

© Copyright 2003-2016 Exxon Mobil Corporation. All Rights Reserved.
