

MATERIAL SAFETY DATA SHEET

SECTION 1

PRODUCT AND COMPANY IDENTIFICATION

PRODUCT

Product Name:MOBILGREASE XHP 322 MINEProduct Description:Base Oil and AdditivesProduct Code:2015A0202545, 531293-00, 97AB71Intended Use:Grease

COMPANY IDENTIFICATION

Supplier:

EXXON MOBIL CORPORATION 3225 GALLOWS RD.

FAIRFAX, VA. 22037 24 Hour Health Emergency Transportation Emergency Phone ExxonMobil Transportation No. Product Technical Information MSDS Internet Address USA 609-737-4411 800-424-9300 281-834-3296 800-662-4525, 800-947-9147 http://www.exxon.com, http://www.mobil.com

SECTION 2 COMPOSITION / INFORMATION ON INGREDIENTS

Reportable Hazardous Substance(s) or Complex Substance(s)

Name	CAS#	Concentration*
MOLYBDENUM (IV) SULFIDE	1317-33-5	5 - 10%
PHOSPHORODITHOIC ACID, O,O-DI C1-14-ALKYL	68649-42-3	1 - 2.5%
ESTERS, ZINC SALTS (2:1) (ZDDP)		

* All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.

SECTION 3

HAZARDS IDENTIFICATION

This material is not considered to be hazardous according to regulatory guidelines (see (M)SDS Section 15).

POTENTIAL HEALTH EFFECTS

Low order of toxicity. Excessive exposure may result in eye, skin, or respiratory irritation. High-pressure injection under skin may cause serious damage.

NFPA Hazard ID:	Health:	0	Flammability:	1	Reactivity:	0
HMIS Hazard ID:	Health:	0	Flammability:	1	Reactivity:	0

NOTE: This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.



Product Name: MOBILGREASE XHP 322 MINE Revision Date: 29 Jun 2012 Page 2 of 10

SECTION 4

FIRST AID MEASURES

INHALATION

Under normal conditions of intended use, this material is not expected to be an inhalation hazard.

SKIN CONTACT

Wash contact areas with soap and water. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

EYE CONTACT

Flush thoroughly with water. If irritation occurs, get medical assistance.

INGESTION

First aid is normally not required. Seek medical attention if discomfort occurs.

SECTION 5

FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Appropriate Extinguishing Media: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

Inappropriate Extinguishing Media: Straight Streams of Water

FIRE FIGHTING

Fire Fighting Instructions: Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

Hazardous Combustion Products: Smoke, Fume, Aldehydes, Sulfur oxides, Incomplete combustion products, Oxides of carbon

FLAMMABILITY PROPERTIES

Flash Point [Method]: >246°C (475°F) [EST. FOR OIL, ASTM D-92 (COC)] Flammable Limits (Approximate volume % in air): LEL: N/D UEL: N/D Autoignition Temperature: N/D

SECTION 6

ACCIDENTAL RELEASE MEASURES

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. US regulations require reporting releases of this material to the environment which exceed the applicable reportable quantity or oil spills which could reach any waterway including intermittent dry creeks. The

Ex on Mobil

Product Name: MOBILGREASE XHP 322 MINE Revision Date: 29 Jun 2012 Page 3 of 10

National Response Center can be reached at (800)424-8802.

PROTECTIVE MEASURES

Avoid contact with spilled material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders. For emergency responders: Respiratory protection: respiratory protection will be necessary only in special cases, e.g., formation of mists. Half-face or full-face respirator with filter(s) for dust/organic vapor or Self Contained Breathing Apparatus (SCBA) can be used depending on the size of spill and potential level of exposure. If the exposure cannot be completely characterized or an oxygen deficient atmosphere is possible or anticipated, SCBA is recommended. Work gloves that are resistant to hydrocarbons are recommended. Gloves made of polyvinyl acetate (PVA) are not water-resistant and are not suitable for emergency use. Chemical goggles are recommended if splashes or contact with eyes is possible. Small spills: normal antistatic work clothes are usually adequate. Large spills: full body suit of chemical resistant, antistatic material is recommended.

SPILL MANAGEMENT

Land Spill: Scrape up spilled material with shovels into a suitable container for recycle or disposal.

Water Spill: Stop leak if you can do it without risk. Confine the spill immediately with booms. Warn other shipping. Skim from surface.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

ENVIRONMENTAL PRECAUTIONS

Prevent entry into waterways, sewers, basements or confined areas.

SECTION 7

HANDLING AND STORAGE

HANDLING

Prevent small spills and leakage to avoid slip hazard.

Static Accumulator: This material is not a static accumulator.

STORAGE

Do not store in open or unlabelled containers.

SECTION 8

EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMIT VALUES

Exposure limits/standards (Note: Exposure limits are not additive)

Source	Form	Limit / Star	ndard	NOTE	Source
MOLYBDENUM (IV) SULFIDE [as Mo]	Total dust.	TWA	15 mg/m3	N/A	OSHA Z1
MOLYBDENUM (IV) SULFIDE [as Mo]	Inhalable	TWA	10 mg/m3	N/A	ACGIH
	fraction.				
MOLYBDENUM (IV) SULFIDE [as Mo]	Respirable	TWA	3 mg/m3	N/A	ACGIH



Product Name: MOBILGREASE XHP 322 MINE Revision Date: 29 Jun 2012 Page 4 of 10

traction			
fraction.			

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

No special requirements under ordinary conditions of use and with adequate ventilation.

PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

No protection is ordinarily required under normal conditions of use and with adequate ventilation.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

Hand Protection: Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

No protection is ordinarily required under normal conditions of use.

Eye Protection: If contact is likely, safety glasses with side shields are recommended.

Skin and Body Protection: Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

No skin protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact.

Specific Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit



Product Name: MOBILGREASE XHP 322 MINE Revision Date: 29 Jun 2012 Page 5 of 10

emissions.

SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

GENERAL INFORMATION

Physical State:SolidForm:Semi-fluidColor:BrownOdor:CharacteristicOdor Threshold:N/D

IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION Relative Density: N/D Flash Point [Method]: >246°C (475°F) [EST. FOR OIL, ASTM D-92 (COC)] Flammable Limits (Approximate volume % in air): LEL: N/D UEL: N/D Autoignition Temperature: N/D **Boiling Point / Range:** > 316°C (600°F) [Estimated] Vapor Density (Air = 1): N/D Vapor Pressure: < 0.013 kPa (0.1 mm Hg) at 20 °C [Estimated] Evaporation Rate (n-butyl acetate = 1): N/D pH: N/A Log Pow (n-Octanol/Water Partition Coefficient): > 3.5 [Estimated] Solubility in Water: Negligible Viscosity: 320 cSt (320 mm2/sec) at 40 °C Oxidizing Properties: See Hazards Identification Section.

OTHER INFORMATION

Freezing Point:N/DMelting Point:N/DDMSO Extract (mineral oil only), IP-346:< 3 %wt</th>Decomposition Temperature:N/D

NOTE: Most physical properties above are for the oil component in the material.

SECTION 10 STABILITY AND REACTIVITY

STABILITY: Material is stable under normal conditions.

CONDITIONS TO AVOID: Excessive heat. High energy sources of ignition.

MATERIALS TO AVOID: Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: Material does not decompose at ambient temperatures.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11

TOXICOLOGICAL INFORMATION



Product Name: MOBILGREASE XHP 322 MINE Revision Date: 29 Jun 2012 Page 6 of 10

ACUTE TOXICITY	
Route of Exposure	Conclusion / Remarks
Inhalation	
Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Irritation: No end point data for material.	Negligible hazard at ambient/normal handling temperatures. Based on assessment of the components.
Ingestion	
Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Skin	
Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Irritation: No end point data for material.	Negligible irritation to skin at ambient temperatures. Based on assessment of the components.
Eye	
Irritation: No end point data for material.	May cause mild, short-lasting discomfort to eyes. Based on assessment of the components.

CHRONIC/OTHER EFFECTS

Contains:

Base oil severely refined: Not carcinogenic in animal studies. Representative material passes IP-346, Modified Ames test, and/or other screening tests. Dermal and inhalation studies showed minimal effects; lung non-specific infiltration of immune cells, oil deposition and minimal granuloma formation. Not sensitizing in test animals.

Additional information is available by request.

The following ingredients are cited on the lists below: None.

	REGULATORY LISTS SEAF	RCHED
1 = NTP CARC	3 = IARC 1	5 = IARC 2B
2 = NTP SUS	4 = IARC 2A	6 = OSHA CARC

SECTION 12

ECOLOGICAL INFORMATION

The information given is based on data available for the material, the components of the material, and similar materials.

ECOTOXICITY

Material -- Not expected to be harmful to aquatic organisms.

MOBILITY

Base oil component -- Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

PERSISTENCE AND DEGRADABILITY

Biodegradation:

Base oil component -- Expected to be inherently biodegradable



Product Name: MOBILGREASE XHP 322 MINE Revision Date: 29 Jun 2012 Page 7 of 10

BIOACCUMULATION POTENTIAL

Base oil component -- Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

SECTION 13

DISPOSAL CONSIDERATIONS

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

DISPOSAL RECOMMENDATIONS

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

REGULATORY DISPOSAL INFORMATION

RCRA Information: The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed as hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrositivity or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

Empty Container Warning Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

	SECTION 14	TRANSPORT INFORMATION	
--	------------	-----------------------	--

- LAND (DOT): Not Regulated for Land Transport
- LAND (TDG): Not Regulated for Land Transport
- **SEA (IMDG):** Not Regulated for Sea Transport according to IMDG-Code
- AIR (IATA): Not Regulated for Air Transport

SECTION 15 REGULATORY INFORMATION

OSHA HAZARD COMMUNICATION STANDARD: When used for its intended purposes, this material is not classified as hazardous in accordance with OSHA 29 CFR 1910.1200.



Complies with the following national/regional chemical inventory requirements:: AICS, IECSC, PICCS, TSCA Special Cases:

Inventory	Status
NDSL	Restrictions Apply

EPCRA SECTION 302: This material contains no extremely hazardous substances.

SARA (311/312) REPORTABLE HAZARD CATEGORIES: None.

SARA (313) TOXIC RELEASE INVENTORY:

Chemical Name	CAS Number	Typical Value
PHOSPHORODITHOIC ACID,	68649-42-3	1 - 2.5%
O,O-DI C1-14-ALKYL ESTERS,		
ZINC SALTS (2:1) (ZDDP)		

The following ingredients are cited on the lists below:

Chemical Name	CAS Number	List Citations
MOLYBDENUM (IV) SULFIDE	1317-33-5	1, 4, 13, 16, 19
NAPHTHENIC ACIDS, ZINC	12001-85-3	15
SALTS		
PHOSPHORODITHOIC ACID,	68649-42-3	13, 15, 17
O,O-DI C1-14-ALKYL ESTERS,		
ZINC SALTS (2:1) (ZDDP)		
ZINC NEODECANOATE	27253-29-8	15

--REGULATORY LISTS SEARCHED--

6 = TSCA 5a2	11 = CA P65 REPRO	16 = MN RTK
7 = TSCA 5e	12 = CA RTK	17 = NJ RTK
8 = TSCA 6	13 = IL RTK	18 = PA RTK
9 = TSCA 12b	14 = LA RTK	19 = RI RTK
10 = CA P65 CARC	15 = MI 293	
	7 = TSCA 5e 8 = TSCA 6 9 = TSCA 12b	7 = TSCA 5e 12 = CA RTK 8 = TSCA 6 13 = IL RTK 9 = TSCA 12b 14 = LA RTK

Code key: CARC=Carcinogen; REPRO=Reproductive

SECTION 16 OTHER INFORMATION			
N/D = Not determined, N/A = Not applicable			

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

Revision Changes: Section 06: Notification Procedures - Header was modified. Section 01: Product Code was modified.



Product Name: MOBILGREASE XHP 322 MINE Revision Date: 29 Jun 2012 Page 9 of 10

Section 10 Stability and Reactivity - Header was modified.

Section 13: Disposal Recommendations - Note was modified. Section 13: Empty Container Warning was modified. Section 09: Phys/Chem Properties Note was modified. Section 09: Boiling Point C(F) was modified. Section 09: n-Octanol/Water Partition Coefficient was modified. Section 08: Comply with applicable regulations phrase was modified. Section 08: Personal Protection was modified. Section 08: Hand Protection was modified. Section 09: Vapor Pressure was modified. Section 07: Handling and Storage - Handling was modified. Section 11: Dermal Lethality Test Data was modified. Section 11: Dermal Lethality Test Comment was modified. Section 11: Oral Lethality Test Data was modified. Section 11: Inhalation Lethality Test Data was modified. Section 11: Dermal Irritation Test Data was modified. Section 11: Eye Irritation Test Data was modified. Section 11: Oral Lethality Test Comment was modified. Section 11: Inhalation Irritation Test Data was modified. Section 05: Hazardous Combustion Products was modified. Section 06: Accidental Release - Spill Management - Water was modified. Section 09: Flash Point C(F) was modified. Section 09: Viscosity was modified. Section 14: Sea (IMDG) - Header was modified. Section 14: Air (IATA) - Header was modified. Section 14: LAND (TDG) - Header was modified. Section 14: LAND (DOT) - Header was modified. Composition: Component table was modified. Section 15: List Citations Table was modified. Section 15: List Citation Table - Header was modified. Section 14: LAND (DOT) - Default was modified. Section 14: LAND (TDG) Default was modified. Section 14: Sea (IMDG) - Default was modified. Section 14: Air (IATA) - Default was modified. Section 15: National Chemical Inventory Listing - Header was modified. Section 15: SARA (313) TOXIC RELEASE INVENTORY - Table was modified. Section 15: National Chemical Inventory Listing was modified. Section 16: Code to MHCs was modified. Section 15: Community RTK - Header was modified. Section 08: Exposure limits/standards was modified. Section 15: OSHA Hazard Communication Standard was modified. Hazard Identification: OSHA - May be Hazardous Statement was modified. Section 06: Notification Procedures was modified. Section 08: Exposure Limits Table was modified. Section 09: Oxidizing Properties was modified. Section 08: OEL Table - Notation Column - Header was modified. Section 08: Exposure Limit Values - Header was modified. Section 01: Company Contact Methods Sorted by Priority was modified. Section 06: Protective Measures was added. Section 06: Accidental Release - Protective Measures - Header was added. Section 15: Special Cases - Header was added. Section 15: Special Cases Table was added.



Product Name: MOBILGREASE XHP 322 MINE Revision Date: 29 Jun 2012 Page 10 of 10

Section 15: Inventory - Header was added. Section 15: Status - Header was added. Section 09: Decomposition Temperature was added. Section 09: Decomposition Temp - Header was added. Section 09: Vapor Pressure was added. Section 15: TSCA Class 2 Statement was deleted.

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

	Use Only MHC: 0B, 0B, 0, 0, 0, 0	PPEC: A
DGN:	7049633XUS (1009422)	

Copyright 2002 Exxon Mobil Corporation, All rights reserved